

F-301 / F-301K

3 inch thermal printer with auto cutter in panel mounting



F-301 / F-301K

3 inch thermal printer with auto cutter in panel mounting

F-301 : roll bucket opening by pressing button
F-301K : roll bucket opening by pulgging in key

Feature

- Brand name printer mechanism and auto cutter
- Super big roll bucket diameter Max 80 mm
- Compact front panel mounting
- Ultra high printing speed max 200 mm/s
- Unique heat dissipation system
- Multiple panel LED indication
- Available customization case color

Application

Queue management system, Visitor attendance terminal, Ticket vendor, POS, Medical instrument, Body scales and more...



80 mm.



200 mm./s



640 D/L



Autocut



Model : F-301 / F-301K Specification



Mechanism

Printing Method	Thermal dot line
Dot / Line	640 dot/line
Resolution	8 dot / mm
Printing Speed	200 mm/s
Paper width	80 mm
Printing width	80 mm
Paper roll diameter (max)	80 mm
Paper thickness	60-80 Micron
Paper loading method	Easy loading
Auto cutting	YES

Sensor

Printer Head	Thermistor
Paper end	Photo-interrupter

Power feature

Working coltage (Vp)	24 VDC
Power consumption	1.75A (average)
Peal current	4.64A

Environment

Working temperature	-5 ~ 45 °C
Working humidity	20 ~ 85 %RH
Storage Temperature	-20 ~ 60 °C
Storage humidity	5 ~ 95 %RH

Reliability

Cutter life	up to 1,200,000 cuts (Depend on paper thickness)
Pulse	100,000,000
Printing length	up to 1,500,000 m (150 km)

Property

Dimension	84 x 139 x 186 mm	
Weight	FPT-301 : 760 g	FPT-301K : 760 g

Support

Interface	USB or RS-232C
Command	ESC / POS
Driver	Windows / Linux / Android

FMT Coroporation Co.,Ltd.

49/293 Soi Vibhavadi-Rangsit 64 Yeak 13,
 Talat Bangkhen, Lak Si, Bangkok 10210 Thailand
 Tel 662-5218155-59, Fax 662-5217156-7

Website : www.fmtcorp.co.th, E-mail : fmt_sales@hotmail.com

